

**INFS 767**  
**Secure Electronic Commerce**  
**Fall 1999**

**Lecture 8**  
**Unlinkable Serial Transactions**

**Prof. Ravi Sandhu**

**CASE STUDY OF AN ELECTRONIC  
COMMERCE PROTOCOL**

- ◆ **Unlinkable Serial Transactions: Protocols and Application**  
by  
**Stubblebine, Syverson and Goldschlag**
- ◆ **Paper to appear in November 1999 issue of ACM Transactions on Information and System Security (TISSEC)**

## CONFLICTING OBJECTIVES

- ◆ **Provider expects**
  - to be paid
  - to prevent subscription cloning
  - to terminate rogue subscriptions
- ◆ **Customer expects**
  - privacy of usage profile

© Ravi Sandhu 1999

3

## CHAUM'S SOLUTIONS (1981 on)

- ◆ **Payment is by anonymous e-cash**
- ◆ **Customers register using anonymous pseudonyms**

© Ravi Sandhu 1999

4

## CHAUM'S SOLUTIONS (1981 on)

- ◆ **Cannot accommodate credit card payments**
- ◆ **Pseudonyms are a single point of anonymity failure**
- ◆ **Rogue customer can re-register using different pseudonym**

© Ravi Sandhu 1999

5

## UST SOLUTION

- ◆ **customer may be known to vendor but behavior is untraceable**
- ◆ **independent of payment mechanism**
- ◆ **no single point of anonymity failure**
- ◆ **makes subscription cloning difficult**
- ◆ **does not allow multiple concurrent transactions from a single customer**

© Ravi Sandhu 1999

6

## UST SOLUTION

- ◆ **A legitimate subscriber can set up a proxy pirate server**
  - **not a problem in small scale**
    - requires technical skill
    - little motivation
  - **on large scale**
    - can use detect and prosecute strategy to deter

© Ravi Sandhu 1999

7

## BASIC IDEA

- ◆ **Customer gets a one-time unlinkable token**
- ◆ **Fresh token is generated after every use**

© Ravi Sandhu 1999

8

## MAJOR CAVEAT

- ◆ **Cryptographic protocol cannot prevent against linkage through application data**
- ◆ **Trade-off between functionality and anonymity**

© Ravi Sandhu 1999

9

## APPLICATIONS

- ◆ **Subscription to on-line information service**
- ◆ **pay-per-use**
- ◆ **pay-per-view**
- ◆ **multivendor packages (digital coupon books)**
- ◆ **anonymous proof of membership**

© Ravi Sandhu 1999

10

## OPERATING ENVIRONMENT ASSUMPTIONS

- A1. Anonymity protected network communications are unlinkable to prior communications provided application content does not enable linkage.**
- A2. Entities may collude. However, we assume that collusion among customers is insignificant in the sense that there will always be a sufficient number of non-colluding customers and associated transactions to mask legitimate customer activity.**

© Ravi Sandhu 1999

11

## OPERATING ENVIRONMENT ASSUMPTIONS

- A3. We assume that cryptographic keys, nonces, blinding factors, etc. are adequately randomly chosen from an adequately large space to prevent random collisions or revealing of secrets by cryptanalytic attacks.**
- A4. We assume that keyed cryptographic operations prevent any undetectable modification of fields to which those operations are applied. Furthermore, we assume the inability of an entity to forge signatures without knowledge of the key.**

© Ravi Sandhu 1999

12

## OPERATING ENVIRONMENT ASSUMPTIONS

**A5. We assume that every message is received as sent after a finite number of attempts to send it.**

**A6. The vendor will provide services for which he accepts payment.**

## FRAUD REQUIREMENTS

**R1. Eliminate high volume fraud**

**R2. Detect, and reduce activity related to low volume fraud.**

**R3. Payments (including refunds if applicable) cannot be stolen.**

## CUSTOMER PRIVACY REQUIREMENTS

**R4. Protect the identity of the customer in a transaction from vendors, other customers, and outsiders.**

**R5. Prevent the building of customer profiles (including pseudonymous profiles) by vendors, other customers, and outsiders.**

## SERVICE GUARANTEE REQUIREMENTS

**R6. Customers cannot be denied service for which they contracted.**



## NOTATION

$[X]_K$ : Message integrity of X using K

$\{X\}_K$ : Message integrity and confidentiality of X using K

$\underline{X}$ : Blinding of X

$h(X)$ : Hash of X

© Ravi Sandhu 1999

17

## BLINDING

- ◆  $\underline{X}$  is computed from X using a secret blinding factor by Alice
- ◆  $[\underline{X}]_B$  is signed by Bob's private key
- ◆ Alice removes blinding factor by use of secret to get  $[X]_B$
- ◆ Without secret blinding factor cannot associate  $\underline{X}$  with X or  $[X]_B$

© Ravi Sandhu 1999

18

## UST REGISTRATION

- M1. C -> V: {Payment,  $K_{CV}$ }<sub>V</sub>,**  
[Request for certificate of type S, C, h(N1)]  $K_{CV}$
- M2. V -> C: [ h(N1) ]<sub>S</sub>**
- M3. C -> V: [ Ack ]  $K_{CV}$**

© Ravi Sandhu 1999

19

## UST REGISTRATION

- ◆ **Multiple certificates are required if customer needs to access from multiple machines**
- ◆ **Alternately customer can use single certificate at some web page through which all access is proxied**
  - **customer must trust web page host**
- ◆ **Customer authentication is not part of this protocol**

© Ravi Sandhu 1999

20

## CERTIFICATE REDEMPTION

- M1. C -> V: { [h(Ni)]<sub>S</sub>, Ni, K<sub>CV</sub> }<sub>V</sub>,  
[Request for transaction of type S, h(Ni+1)]K<sub>CV</sub>**
- M2. V -> C: [Approved OR Not Approved]K<sub>CV</sub>**
- M3. C <-> V: [Transaction]K<sub>CV</sub>**
- M4. V -> C: [ h(Ni+1) ]<sub>S</sub>**
- M5. C -> V: [Ack]K<sub>CV</sub>**

© Ravi Sandhu 1999

21

## CERTIFICATE REDEMPTION

- ◆ **New certificate is obtained after transaction ends**
  - makes it harder for subscriber to run proxy subscription service
- ◆ **K<sub>CV</sub> is used for integrity protection in protocol**
  - can optionally be used for confidentiality protection
  - C has incentive to choose it to be unique
  - use of K<sub>CV</sub> has to be serialized within a transaction otherwise sharing of K<sub>CV</sub> can lead to concurrent use by sharing K<sub>CV</sub> instead of sharing certificate

© Ravi Sandhu 1999

22

## NOT APPROVED

- ◆ [Not Approved] $K_{CV}$  is sent only if nonce does not match signed certificate
- ◆ other Not Approved errors sent without  $K_{CV}$
- ◆ makes protocol fail-stop

© Ravi Sandhu 1999

23

## SUBSCRIPTION TERMINATION

- M1. C  $\rightarrow$  V: {  $[h(Ni)]_S$ , Ni,  $K_{CV}$  }<sub>V</sub>,  
[Request for transaction of type S terminate, C ] $K_{CV}$
- M2. V  $\rightarrow$  C: {Refund} $K_{CV}$  OR  
[Not approved] $K_{CV}$
- M3. C  $\rightarrow$  V: [Ack] $K_{CV}$

© Ravi Sandhu 1999

24

## SUBSCRIPTION TERMINATION

- ◆ **May require multiple certificates to be returned**
- ◆ **refund can take any form: e-cash, credit card, paper check**
- ◆ **customer authentication (for refund) is not part of this protocol**
- ◆ **termination by vendor is not so easy: requires change of service key S**

© Ravi Sandhu 1999

25

## RECOVERY

- ◆ **Broken connection**
  - **if protocol breaks too early can replay in entirety (except for transaction)**
  - **ack is assumed after suitable time-out**
  - **registration gets committed after ack (explicit or assumed)**
- ◆ **Disk crash**
  - **reinitialize**
  - **backup certificates**

© Ravi Sandhu 1999

26

## SERVICE KEYS

- ◆ **Service key S should be well known to prevent selection on per-subscriber basis**
- ◆ **S can be changed to terminate subscriptions**

© Ravi Sandhu 1999

27

## SUBSCRIPTION SHARING

- ◆ **Certificate sharing**
- ◆ **proxy server**
- ◆ **session sharing**

© Ravi Sandhu 1999

28

## UST WITH AUDIT (USTA) REGISTRATION

- M1. C -> V: {Payment,  $I_{\text{audit}}$ ,  $K_{CV}$ }<sub>V</sub>,**  
[Request for certificate of type S, C,  $h(N1)$ ]  $K_{CV}$
- M2. V -> C: [  $h(N1)$  ]<sub>S</sub>**
- M3. C -> V: [ Ack ]  $K_{CV}$**

© Ravi Sandhu 1999

29

## USTA CERTIFICATE REDEMPTION

- M1. C -> V: { [  $h(Ni)$  ]<sub>S</sub>,  $Ni$ ,  $K_{CV}$  }<sub>V</sub>,**  
[Request for transaction of type S,  
 $h(Ni, I_{\text{audit}}, \text{Salt}), \underline{h(Ni+1)}$ ]  $K_{CV}$
- M2. V -> C: [Approved OR Not Approved OR Audit]  $K_{CV}$**
- M3. C <-> V: [Transaction]  $K_{CV}$**
- M4. V -> C: [  $h(Ni+1)$  ]<sub>S</sub>**
- M5. C -> V: [Ack]  $K_{CV}$**

© Ravi Sandhu 1999

30

## AUDIT PROTOCOL

- M1. C -> V: { [h(Ni)]<sub>S</sub>, Ni, K<sub>CV</sub> }<sub>V</sub>,**  
[Request for transaction of type S,  
h(Ni, I<sub>audit</sub>, Salt), h(Ni+1) ]K<sub>CV</sub>
- M2. V -> C: [Audit]K<sub>CV</sub>**
- M3. C -> V: {C, Ni, I<sub>audit</sub>, Salt} K<sub>CV</sub>**
- M4. V -> C: [ h(Ni+1) ]<sub>S</sub> OR**  
[Not approved]K<sub>CV</sub>
- M5. C -> V: [Ack]K<sub>CV</sub>**

© Ravi Sandhu 1999

31

## AUDIT PROTOCOL

- ◆ **Must use K<sub>CV</sub> and not V in message 3**

© Ravi Sandhu 1999

32



## APPLICATIONS

- ◆ **Pay-per-use (digital tokens)**
- ◆ **third party subscription management**
- ◆ **multivendor packages**
- ◆ **membership and voting**

© Ravi Sandhu 1999

33

## RELATED WORK

- ◆ **Digital cash**
- ◆ **Anonymity services**

© Ravi Sandhu 1999

34